



HIPOTRONICS[®]
THE MEASURE OF A LEADER

800PL Series DC Hipot Testers

KEY FEATURES

- Rugged and portable
- One-piece construction
- Shielded output cable
- Guard circuit
- Full-wave voltage doubling rectifier circuit
- Zero start interlock
- Internal discharge on HV OFF
- Meter accuracy $\pm 2\%$ full scale
- 5 mA current rating for cable charging
- External interlock provisions
- Three range voltmeter
- Four range current meter
- No internal leakage at full load
- Instantaneous overload relay
- Surge-limiting resistors in HV output

BENEFITS

- Ideal for field testing – lightweight, compact, and rugged
- Safe and easy operation
- No exposed high voltage
- Accurate leakage current measurement
- Guard circuit eliminates stray leakage currents

APPLICATIONS

DC Hipot testing of:

- cable
- transformers
- electrical switchgear
- motors
- generators
- other electrical apparatus




*Model 880PL
DC Hipot Tester*

DESCRIPTION

The 800PL Series DC hipot testers provide an economical solution to DC field testing of cables, terminations, motors, generators and other electrical apparatus. Models 815PL and 880PL offer 15kV or 80kV respectively. All models are self contained in a single rugged and durable enclosure which is complete from input line cord to high voltage output cable. Cables are conveniently stored inside the case.

The 800 Series testers feature accurate kV meter readings regardless of load current. Accurate voltage and current measurements are assured since voltage readings are taken directly at the output of the high voltage transformer and current measurements are taken in the return leg. Safe discharging of both the test object and the high voltage transformer occur whenever the high voltage is turned off. Output power is provided by means of a full-wave voltage doubling rectifier circuit with silicon rectifiers.



800 PL Panel Detail

SPECIFICATIONS

INPUT VOLTAGE		Model number suffix -A	120 V / 60 Hz
		Model number suffix -B	220 V / 50 Hz
MODEL		815PL	880PL
OUTPUT VOLTAGE		0 - 15 kV	0 - 80 kV
OUTPUT CURRENT		5 mA	5 mA
WEIGHT	Net.	47 lb (21 kg)	76 lb (34 kg)
	Ship.	57 lb (26 kg)	86 lb (39 kg)
POLARITY		Negative output, positive ground	
METERING		± 2% full scale accuracy	
RIPPLE		Less than 2.5%	
DIMENSIONS		18" W x 13" D x 13" H (46 x 33 x 33 cm)	
CABLES AND CORDS		Input Line Cord	6 ft (1.8 m) 3 wire & plug, grounded type
		Return Cable	25 ft (7.6 m)
		High Voltage Output Cable	25 ft (7.6 m) shielded RG34/U w/alligator clip & rubber insulated boot

ACCESSORIES

- Spare Parts Kits – Catalog Nos. SPK1-815PL, SPK1-880PL

For further information, contact:

Hipotronics, Inc.

A Subsidiary of Hubbell, Incorporated
Route 22, P. O. Box 414
Brewster, NY 10509, U.S.A.

1-800-727-4476

Tel: 845-279-8091

Fax: 845-279-2467

NOTE: Because Hipotronics has a policy of continuous product improvement, it reserves the right to change design and specifications without notice.