N9021B MXA Signal Analyzer 10 Hz to 8.4/513.6/26.5/32/44/50 GHz



Quickly Adapt to Evolving Test Requirements

Industries from wireless to satellite communications require wider analysis bandwidth to meet demands for higher data throughput. As higher bandwidth technologies such as 5G NR move into mainstream use, engineers need tools for design validation and manufacturing that offer the accuracy, speed, and bandwidth to accelerate device development.

Keysight's new N9021B MXA Signal Analyzer offers best-inclass bandwidth and phase noise for accurate and repeatable signal analysis across millimeter-wave and 5G NR frequencies.

Keysight sees a great synergy between TRS-RenTelco as the enabler in facilitating innovations with comprehensive test equipment and Keysight as a leading test and measurement equipment provider.

TRS-Rentelco offers Keysight hardware and software solutions as rental options for customers who prefer not to own.

"As part of the partnership, we are collaborating to launch the new Keysight MXA N9021B and PXA N9032B at IMS 2022. TRS-Rentelco offers the whole range of Keysight X-Series Signal Analyzers, with the addition of the new Keysight N9021B wideband MXA that enables higher data throughput with wider bandwidth up to 510 MHz, wireless communication customers now have a mid-range analyzer optimized for wireless DVT and manufacturing."

- Garrett Gregg, Keysight Global Rental Partner Program Manager

Keysight N9021B MXA X-Series Signal Analyzer

The optimum choice in wireless for new generation devices.

See the real performance of your device

- R&D, design validation (DVT) and manufacturing engineers need to keep up with the rapidly expanding wireless industry into wider bandwidth, enabling higher data throughput demand, and millimeter wave (mmWave) frequencies including 5G New Radio (NR) and high-throughput satellite (HTS) communications, and Wi-Fi 7. Keysight signal analyzers provide reliable results, whether you need deep-dive measurements for solving tough problems in R&D or quick and simple measurements for manufacturing.
- The new N9021B MXA Signal Analyzer provides analysis bandwidth and the superior phase noise performance to meet the needs of engineers designing and delivering today's 5G and wideband wireless applications.









Key performance data

SPECIFICATIONS

Frequency range	10 Hz to 8.4, 13.6, 26.5, 32, 44, and 50 GHz		
Analysis bandwidth	255 MHz, or 510 MHz		
Display average noise level (@3 GHz)	-154 dBm (preamp off), -164 dBm (preamp on)		
Phase noise (10 kHz offset)	-130 dBc/Hz at 1 GHz typical		
Third-order Intermodulation Distortion	+23 dBm at 3 GHz typical		
Real-time bandwidth	Up to 510 MHz		
Amplitude Accuracy	±0.44 dB at 3 GHz, 95% percentile		
Probability of Intercept (POI)	Minimal signal duration of 3.51 μs for 100% POI and full amplitude accuracy		

OPTIONS

Frequency		Preamplifier		Analysis bandwidth	
Option	Description	Option	Description	Option	Description
508	10 Hz – 8.4 GHz	P08	100 kHz – 8.4 GHz	B2X	255 MHz analysis bandwidth
513	10 Hz – 13.6 GHz	P13	100 kHz – 13.6 GHz	B5X	510 MHz analysis bandwidth
526	10 Hz – 26.5 GHz	P26	100 kHz – 26.5 GHz		
532	10 Hz – 32 GHz	P32	100 kHz – 32 GHz		
544	10 Hz – 44 GHz	P44	100 kHz – 44 GHz		
550	10 Hz – 50 GHz	P50	100 kHz – 50 GHz		
				X @ #: 4	Contraction of the second s

Reliable Signal Analysis Results

Meets evolving test needs of advanced wireless and satellite communications DVT and manufacturing

- Frequency range of 10 Hz 50 GHz, meeting specification requirements for both 5G NR FR1 and FR2
- Detect signals you couldn't see before with extended analysis bandwidth up to 510 MHz and >75 dB SFDR
- Best-in-class RF performance with an SSB phase noise 130 dBc/Hz typical (1 GHz, 10 kHz offset)

Explore every facet of a complex signal and optimize your designs

- Capture elusive or transient signals with a full-band real-time spectrum analyzer (RTSA)
- Use Keysight's powerful industry-leading 89600 PathWave VSA software to validate your design and pinpoint signal issues with signal recording, playback, vector signal analysis, and demodulation support for over 75 industry standard signals.

Repeatable results from software enabled measurement science

- Utilize the PathWave X-Series Applications to measure system or component compliance across multiple parametric or standards-compliant wireless signals.
- Maximize the flexibility of test assets with a wide variety of PathWave X-Series Applications offer licensing terms that enable application sharing between X-Series signal analyzers and PXIe instruments.









